

1.標準型(一)超音波發振機

Standard Type(一) Ultrasonic Generator

Features (特長)

一. 分離式振盪，不受負載影響，輸出穩定。

Isolate the way work, Free of load, Export steadily.

二. 內部分段輸出，匹配容易。

The inside is exported by stage, it is easy to match.

三. 輸出頻率 5%可調整。

It is adjustable to output 5% of frequency.

四. 可選擇單一振盪或多頻掃描輸出。

Can choose single vibration or scan frequently export.

五. 電路簡單，故障率低，維修容易。

The circuit is very simple, low trouble, easy to maintain.



Specification (規格說明)

Model 型號	WB-03N28 WB-03N40	WB-06N28 WB-06N40
Input Voltage 入力電壓	1Ø 100v/220v 1Ø 110v/220v	1Ø 200v 1Ø 220v
Oscillation Frequency 發振週波數	28KHZ/40KHZ	28KHZ/40KHZ
External Dimension 外形寸法(mm)	480(L)*310(W)*170	480(L)*310(W)*170(H)
Weight 重量	11KG	11KG
Power 出力	300W	600W

2.標準型(二)超音波發振機

Standard Type(二) Ultrasonic Generator

Features (特長)

一.分離式振盪，不受負載影響，輸出穩定。

Isolate the way work, Free of load, Export steadily.

二.內部分段輸出，匹配容易。

The inside is exported by stage, it is easy to match.

三.輸出頻率 5%可調整。

It is adjustable to output 5% of frequency.

四.可選擇單一振盪或多頻掃描輸出。

Can choose single vibration or scan frequently export.

五.電路簡單，故障率低，維修容易。

The circuit is very simple, low trouble, easy to maintain.



Specification (規格說明)

Model 型號	WB-09N28 WB-09N40	WB-12N28 WB-12N40
Input Voltage 入力電壓	1Ø 220v	1Ø 220v
Oscillation Frequency 發振週波數	28KHz 40KHz	28KHz 40KHz
External Dimension 外形寸法 mm	510(L)*420(W)*170(H)	510(L)*420(W)*170(H)
Weight 重量	17KG	17KG
Power 出力	900W	1200W

3.標準型(三)超音波發振機

Standard Type(三) Ultrasonic Generator

Features (特長)

一.分離式振盪，不受負載影響，輸出穩定。

Isolate the way work, Free of load, Export steadily.

二.內部分段輸出，匹配容易。

The inside is exported by stage, it is easy to match.

三.輸出頻率 5%可調整。

It is adjustable to output 5% of frequency.

四.可選擇單一振盪或多頻掃描輸出。

Can choose single vibration or scan frequently export.

五.電路簡單，故障率低，維修容易。

The circuit is very simple, low trouble, easy to maintain.



Specification (規格說明)

Model 型號	WB-18N28 WB-18N40	WB-20N28 WB-20N40
Input Voltage 入力電壓	1Ø 220v	1Ø 220v
Oscillation Frequency 發振週波數	28KHz 40KHz	28KHz 40KHz
External Dimension 外形寸法 mm	510(L)*500(W)*170(H)	510(L)*500(W)*170(H)
Weight 重量	20KG	20KG
Power 出力	1800W	2000W

4.交換式雙頻超音波發振機

Switching Dual Frequency Ultrasonic Generator

Features (特長)

一. 兩種頻率交換輸出，清洗效果更佳。

Two kinds of frequency are exchanged, there are better clean results.

二. 適合精密加工件清洗使用。

Most suitable for the accurate part to clean.

三. 去泡功能減少液體流動干擾。

Steep the function, Can reduce the liquid to interfere while flowing.

四. 面板有雙可調功能:輸出功率可調及頻率可微調。

The panel has two kinds of adjustable functions: output power can be adjusted and frequency can be trace adjusting.



Specification (說明)

Model 型號	WB-06DF80 WB-06DF133	WB-09DF80 WB-09DF133
Power 出力	600W	900W
Input Voltage 入力電壓	110V 1Φ 220V 1Φ	110V 1Φ 220V 1Φ
Oscillation Frequency 發振週波數	40KHz/80KHz 40KHz/133KHz	40KHz/80KHz 40KHz/133KHz
External Dimension 外形寸法 mm	355(L)*490(W)*170(H)	355(L)*490(W)*170(H)
Weight 重量	15KG	15KG

5.高頻超音波發振機

High Frequency Ultrasonic Generator

Features (特長)

一. 高頻率，高效能出力。

High frequency, high capacity and efficiency.

二. 適合半導體，鏡片等精密產品。

Clean the target: the semiconductor, the lens, etc..

三. 去泡功能減少液體流動干擾。

Steep the function, Can reduce the liquid to interfere while flowing.

三. 輸出功率可調。

Output power can be adjusted.



Specification (說明)

Model 型號	WB-600 HF68 WB-600 HF80 WB-600 HF100 WB-600 HF133	WB-1200HF68 WB-1200HF80 WB-1200HF100 WB-1200HF133
Power 出力	600W	1200W
Input Voltage 入力電壓	220V 1Φ	220V 1Φ
Oscillation Frequency 發振週波數	68KHz 80KHz 100KHz 133KHz	68KHz 80KHz 100KHz 133KHz
External Dimension 外形寸法 mm	305(L)*465(W)*170(H)	305(L)*465(W)*170(H)
Weight 重量	15KG	15KG

6.掃頻超音波發振機

Sweep Frequency Ultrasonic Generator

Features (特長)

一. 頻率自動掃描。

Automatic scanning of frequency.

二. 輸出功率可調。

Output power can be adjusted.

三. 重量輕，出力大。

Weight is very light, but output power is very strong.



Specification (說明)

Model 型號	WB-600SF28 WB-600SF40	WB-1200SF28 WB-1200SF40
Power 出力	600W	1200W
Input Voltage 入力電壓	1Ø 220v	1Ø 220v
Oscillation Frequency 發振週波數	28KHz 40KHz	28KHz 40KHz
External Dimension 外形寸法(mm)	460(L)*290(W)*170(H)	460(L)*290(W)*170(H)
Weight 重量	11KG	11KG

7. 聚焦式超音波發振機

Focus Type Ultrasonic Generator

Features (特長)

一. 頻率自動追蹤，不會因環境變化而改變效率。

Frequency tracks automatically, efficiency keeps the optimization at any time.

二. 過載保護功能，異常顯示。

Overload protection function, unusually display.

三. 適合紡口，濾管，濾網，模具等需要高振幅振盪之產品洗淨。

Clean the target: textile spray nozzle, filter, press parts, filter screen, mould, etc., need to use the high power to get rid of the dirty and corrupt part.

四. 能量由上往下衝擊，可以採用輸送帶運送連續清洗。

Energy is had assaulting down, can adopt the conveyer belt to transport and wash in succession.



Specification (說明)

Model 型號	WB-22FC15
Power 出力	2200W
Input Voltage 入力電壓	1Ø 220v
Oscillation Frequency 發振週波數	15KHz
External Dimension 外形寸法 mm	580(L)*430(W)*170(H)
Weight 重量	19KG